Provo, Utah, February 11.1915.

To The Honorable A.B. Morgan, Judge: -

In compliance with the order made by Your Honor on December 15th, 1914, the accompanying report is respect-fully submitted.

The data on water measurements contained herein ise are the results of the measurement and distribution made under the direction of your Commissioner during his period of service. The tables of calculated values, showing rates of use and quantities used by most of the larger diversions, are submitted to more clearly bring out these features.

The comments and recommendations are the result of the experience and observation of your Commissioner during the season; and are submitted with the hope that they might be of some value in this litigation.

Your Commissioner was greatly handicapped in the measurement of the flow of some of the canals by the lack of proper measuring devices. In some cases the users neglected to comply with the request to install them; and in the casees not so equipped of the larger canals, the same were not installed on account of the interference it would have with irrigation operations to divert water from the canals at that season of the year.

Respectfully submitted:

Water Commissioner.

WASATCH DIVISION OF PROVO RIVER.

The Wasatch Division of Provo River as defined in the order of the Court in this cause, dated May 25th 1914, includes all diversions from the River at and above the Wasatch Dam In Wasatch County.

There is a total of 51 diversions, which includes the following corporations diverting water at the Wasatch Dam, namely;

Wasatch Irrigation Company, North Field Irrigation Company, Charleston Irrigation Company, Extension Irrigation Company, Sage Brush Irrigation Company,

and the following corporations having separate diversions above this point;

Timpanogas Irrigation Company, Utah Power and Light Company, South Kamas Irrigation Company, Washington Irrigation Company, Sunrise Irrigation Company,

The remaining diversions are those of individuals or associations of individuals using small atreams intermittantly. The total irrigated area is approximately 15,000 acres.

As shown by the report of Deputy Commissioner, George F. Taylor, a copy of which is submitted herewith, most of the diversions, except those diverting at the Wasstch Dam, are equipped with proper measuring devices; so that with a proper determination of the acreage under each diversion and the installation of the few measuring devices where needed, a just distribution can easily be made in this division. Since most of the canals are small, the distribution among these should be by time in order that a comparatively lagge head may be used.

Attached hereto and made a part hereof, is a list of the diversions in this division, with the kind of measuring device, approximate acreage and the measurements reported by Deputy Taylor during the season of 1914.

LIST OF DIVERSIONS
AND
WATER DIVERTED IN 1914.

WASATCH DIVISION OF PROVO RIVER. WASATCH AND SUMMIT COUNTIES.

Diversion No.W-1-a-b-c-d & W-3.

THE STEWART RANCH COMANY? WOODLAND.

Measuring Devices..All have weirs except W=3. approximate acreage....630 acs.

Measurements in 1914.

JUNE	J	ULY	AUG	UST	SEPE	
Day Sec.ft 10 30.30 18 23.03 25 7/70 29 7.50	Day 7 9 14 18 23 31	Sec.ft 11.00 5.00 6.00 9.60 7.00 5.00	Day 1 5 8 10 11 15 20 22 24 27	Sec.ft. 5.00 3.80 0.00 0.00 4.40 2.20 2.20 0.00 0.00	Day	Sec.ft.

Diversion No.w-2.

THE SUNRISE CANAL COMPANY, WOODLAND?

Measureing Device....Good ating Flume. Approximate Acreage....500 acres.

Measurements in 1914.

TII	NE	JULY		AUGU	JST	SEPT	EMBER.
JU Day 10 15 18 25 29	NE Sec.ft. 10.10 11.30 10.40 12.60 12.30	JULY Day 1 8 10 15 18 23	Sec.ft. 12.00 10.90 11.00 8.00 7.20 7.00	AUG Day 1 5 8 11 16 19 21	Sec.ft 6.80 5.20 6.50 6.50 4.80 4.00 4.00 3.80	Day 1 4	Sec ft. 3.00 2.60
				27	3.80		

Diversion No.W-4.

JAMES DUNCAN ET AL.

Measuring evice... Good weir properly located. approximatelyx Acreage.... 40. acs.

			Measurem	ents in 1	914.	CONTRACTOR (MET)	VETER O
	JUNE	J	ULY	A	UGUST	SEPTE	MBERI
Day 25 29	Sec ft. 0.35 0.83	Day 8 10 15 18 23 31	Sec. ft 0.80 0.80 0.30 0.80 0.70 0.50	Day 1 5 No w	Sec ft. 0.50 0.00 ater used	Day after Au	Sec.ft.

Diversion No.W-5.

SOUTH KAMAS IRRIGATION COMPANY.

Measuring Device... Good Rating Flume. Approximately Acreage.....1700 acs.

Measurements in 1914.

JU	NE	JULY	,	I I	AUGUST	S	EPTEMBER.
Day	Sec.ft.	Day	Sec.ft	Day	Sec. ft.	Day	Sec. ft.
4	39.60		36.00	1	33.40	1	14.40
4 5	37.60	3	32.00	5	31.50	7	13.50
99 9	28.80		37.00	8	31.30	10	13.50
10	26.70	7	34.00	12	31.50		
-	34.40	9	36.00	15	30.00		
14	39.00	14	28.00		28.20		
15	40.80	18	32.90	19	29.50		
18	38.00	23	34.00		16.60		
10	36.20		30.00	21	14.50		
25	38.60	31	33.40		16.70		
29	33.00	-	00110	25	18.20		
20	00100				15.70		
				27	16.60		
				30	14.00		
				30	15.70		

特特特特尔特特特特特特特特特特特特特特特特

D 1version No.w-6. WASHINGTON IRRIGATION COMPANY.

Measuring Device....Good Rating Flume. Appreximate Acreage..... 12002 acs.

Measurements in 1914.

	JUNE	JULY		AU	GUST	SEPTEMBER.		
Day	Dec. ft.	Day	Sec.ft.	Day	Sec.ft.	Day	Sec. ft.	
4	26.70	1	26.00	1.	16.00	1	9.10	
5	30.20		28.00	. 5	13.20	7	3.10	
9	17.00	7	21.60	8	11.30	10	2.00	
10	18.00		28.00	12	8.70			
1.4	30.20	10	27.00	16	11.00			
15	30.20	15	5.60		2.00			
25	27.00	18	18.50	19	14.60			
29	13.40	23	26.50	21	14.60			
			11.50	24	14.40			
		31	16.00	27	14.40			
				30	11.40			
					14 40			

Diversion No.W-7.

PHILLIPS DITCH.

Water is taken from the washington Canal in five places Measuring Devices five weirs. approximate Acreage...... 71.5 acs.

	JUNE	Me	asurements LY	in 193		SEPT	EMBER.
Day	Sec.ft.	Day 1 8 10 15 18 23 31	Sec.ft. 5.00 1.40 2.50 1.20 2.40 1.80 0.90	Day 1 5 8 12 16 20 22 25 28	Sec.ft 0.90 2.00 1.20 1.30 2.30 1.70 1.70 2.00 1.80	Day 1 2 7 10	Sec. ft. 1.30 1.30 1.10 1.10
			** ** ** ** ** ** **	30 *****	1.40		

THOMAS WHITE CANAL.

Measuring devices None. approximate Acreage.., Unknown.

Measurements in 1914

JUNE		JULY	AUGUST SEPTEMBER.
Day Sec. ft.	Day 10	Sec. ft. 1.00	Day Sec. ft. Day Sec.ft. No water taken after July 18th.
Sub-irrigated.	16 18	0.00	
		******	***

Diversion No.w-9.

UPPER MOON DITCH.

Measuring Device Good weir properly located. Approximate Acreage 45 acs.

Measurements in 1914.

JU	INE	JU	LY		AUGUST		SEP	PEMBEI	R
Day Sub-i	Sec.ft Irrigated	Day 8 10	Sec.ft. 1.20 1.30	Day	Sec.ft		Day	Sec.	
		15 18	1.70		No water	taken	after	July	31.
		23 31	1.20	er de de de de de de de	45 12 26 45 15 05 26 46				

Diversion No.10 W.

FITZGERALD AND HARDMAN CANAL.

Measuring Device.... Good Rating Flume properly located. approximately acreage... Unknown.

Measurements in 1914.

JUNE	J	JULY		UGUST	SEPTEMBER.	
Day Sec.ft	Day	Sec.ft	Day	Sec. ft.	Day	Sec.ft.
Sub-irrigated.	7	1.00	i	0.70		
	9	1.50	6	0.80		
	14	2.00	9	0.00		
	18	0.80	1.3	0.00		
	23	1.00	17	0.00		
	31	0.70	20	0.00		
			22	0.00		
			25	1.70		
			28	0.50		
			30	0.40		
		******		46 46 46 46 46 46 46 46 46		

Diversion No.W-11.

LOWER MOON DITCH. Measuring Device....Good weir properly located. approximate Acreage..... 72 acs.

		Measureme		1914.		
JUNE	JULY		AUGUS!	T	SEPTEM	BER
Day Sec.ft.	Day	Sec. ft.	Day	Sec. ft.	Day	Sec. ft.
Sub-irrigated.	8	1.00	1	0.60		
	10	1.00	6	0.20		
	15	0.80	9	0.00		
	18	0.50	13	0.70		
	23	0.50	17	0.10		
	31	0.60	20	0.40		
			22	0.10		
			25	0.20		
			28	0.10		
			30	0.00		

CUTLER DITCH.

Measuring Device.....Good Rating Flume properly located.

Approximate Acreage...... 22 270(?)acs.

Measurements in 1914.

THNE	JULY		A	UGUST	SEP	TWMBER.
JUNE Day Sec.ft	Day 7 10 15 18 23 31	Sec. ft 3.20 0.00 3.20 3.20 3.20 3.00	Day 1 6 9 12 15 19 22 25 28 30	Sec. ft 3.00 3.50 3.40 3.40 2.20 2.80 2.60 2.40 2.60	Day 1 8 10	Sec. ft. 2.00 2.50 2.50
		***	计科科科科科科科	***		

Diversion No. W-14.

TURNBOW AND JINES DITCH.

Measuring Device......Good Rating Flume properly located. Approximate Acreage...... 17.50 acs.

Measurements in 1914.

JUNE	JU	LY	4	AUGU	ST	SEPTEMBER.
Day Sec.ft	Day	Sec.fy 0.80		Day	Sec.ft 2.00	Day Sec.ft.
	7	1.00		6	0.80	No water taken after
	9	0.00		9	0.50	August 15th.
	14	1.00		12	0.50	
	18 23	1.30		15	0.00	
	31	2.00				
	31		. 45 45 45 4	0 40 40 40 40 40 40	* 4 4 4 4 4 4 4 4 4 4 4	

Diversions Nos.w=15-a-b-c-

ETHER WEBB CANALS.

Measuring Devices.... Good weirs in all except 15-c. Approximate Acreage..... 94 acs.

JUNE JULY		AUGUST	SEPTEMBER.		
Day Sec. ft			Day Sec. ft.		
	7 0.00	o water	taken after July 23rd	•	
	9 0.00				
	18 0.00 23 4.60				
		********************	41-44-44-44		

Diversion No.W-13.

JAMES A.KNIGHT CANAL NO L. measuring Device... Good weir properly lovated. Approximate Acreage.....Unknown.

Measurements in 1914.

JUNE		JULY		AUG	UST	SEPTEMBER.		
Day	Sec.ft	Day	Sec.ft.	Day	Sec. ft	Day	Sec. ft.	
4	4.40	1	4.40	1	0.00	1	0.00	
30	0.00	2	0.00	6	0.00	7	1.30	
		7	1.80	9	0.00	10	1.30	
		9	2.00	1.2	0.00			
		13	0.70	16	0.00			
		18	0.00	19	0.00			
		23	0.00	22	0.00			
		31	0.00	25	0.700			
				28	0.70			
				30	0.00			
			36 36 36 36 36 36 36 36 36 36	. 46 26 26 46 46 46 46 4				

Diversion No.w-16.

JAMES A. KNIGHT CANAL NO. 2.

Measuring Device......Good weir properly located. Approximate Acreage..... Unknown.

Measurements in 1914.

JUNE		HULY		AUGUS	T	SEPTEMBER	
Day 14 18 25	Sec.ft. 4.50 4.60 2.03	Day 1 7. 9	Sec.ft 0.00 2.00 1.50	Day 1 6	Sec. ft. 2.00 1.90 1.90	Day Sec. ft.	f-
30	2.03	14 18 23 31	2.00 2.00 3.00 2.00	12	0.00	ter aug. 12.	

Diversion No.W-17.

JAMES A. KNIGHE CANAL NO.3.

Measuring Device....None.

Approximate Acreage.Unknown.

Measurements in 1914.

JUNE JU		JULY		AUG	UST	SEPTEMBER?	
Day 4	Sec.ft.	Day .	Sec.ft 2.00	Day	Sec.ft 0.00	Day Sec.ft.	
30	2.00	7	0.00	6	2.10		
	4.50	9	0.00	9	2.10	No water after	
		18	0.00	18	0.00	aug. 14th.	
		23 31	0.00	22	0.00		

* Note: James A. Knight Claims to irrigate 300 acres from the above canals, (...=13-16 & 17), The acreage under each being unknown.

Diversion No.w-17-a
OLA W. LARSEN GANAL NO L.

Measuring Device.... Good weir properly located. approximate Acreage.... Unknown.

Measurements in 1914.

JUNE	JULY		AU	GUST	CEDMENTER	
Day Sec.ft. 30 1.30	Day 1 8/ 10	Sec.ft. 1.30 0.00 0.00	Day 1 6 9	Sec. ft. 0.50 1.30 1.30	SEPTEMBER. Day Sec. ft. No water after	
July 3 - 1.20	15 18 22 31	0.00 0.00 0.70 0.50	12 15	1.30	Aug. 12 th.	
	**	f * * * * * * * * * * * * * * * * * * *	特特特特特特特	45.45.45.45.46.06		

Diversion No. n-17-b.

OLA W. LARSEN CANAL NO.2.

Measuring Device..... Good weir properly located. Approximate Acreage.... Unknown.

Measurements in 1914.

JUNE		JULY		AUGUST		CEDMENTS	
Day 30	Sec.ft. 1.60	Day 1 8	Sec.ft. 1.60 1.30	Day	Sec.ft	SEPTEMBER. Day Sec.ft.	
		10 15	1.58	1	No water	taken after	
		19	0.00		July 10th	1.	

林林林林林林林林林林林林林林林林林林林林林林林林林林林

Diversion No. 17-c.

OLA W.LARSEN CANAL NO. 3.

Measuring Device..... Good weir properly located. Approximate Acreage..... Unknown.

Measurements in 1914.

JUNE		Jt	JLY	AUGUST	C With the state of the state of the
Day S 3 8 10 15 30	ec.ft. 4.30 1.10 0.00 0.00 2.00 2.00	Day 1 19 22	Sec ft. 2.00 1.70 0.00	Day Sec. ft.	SEPTEMBER. Day Sec.ft. after July 10th.
venston	No. 37 4	*	*****	*****	

Diversion No.17-d.

OLA W. LARSEN CANAL NO 4.

"easuring Device...... Good weir properly located. Approximate Acreage......Unknavn.

Jt	JNE	J	Measureme ULY				
Day 30	Sec. ft 1.70	Day 1	Sec. ft 1.70	AUGU Day	Sec.ft	SEPTWMI Day	Sec.ft
		7 9	0.00	No	water take	n after	r
		15 19	0.40		uly 23rd.		
1 n W	10	23	0.80				

Ola W. larsen claims to irrigate 120 acres from the above 4 camals, (w=17-a-b-c-d=), the acreage under each being unknown.

Diversion No.w.18-a
RASMUS LARSEN CANAL NO. 1.

Measuring Device......Good weir properly located. Approximate AcraegeUnknown.

Measurements in 1914.

AUGUST SEPTEMBER. JUNE JULY Day Sec.ft Sec.ft Day Sec.ft Day Sec.ft Day Measurements taken up to Aug. 10 1.30 8 30 1.20 show no water diverted after July 8th.

Diversion No. 18-b.

BASMUS LARSEN CANAL NO. 2.

Measurements in 1914.

AUGUST SEPTEMBER. JULY JUNE Sec ft. Sec.ft Day Sec. ft. Day Sec.ft Day Day 0100x 0.80 8 0.00 30 "easurements taken up to Aug. 9th show no water diverted after uly 8th *******************************

Diversion No. 18-c.

RASMUS LARSEN CANAL NO. 3.

Measuring Device.........Good weir properly located. approximate Acreage.......Unknown.

Measurements in 1914.

JUNE		JULY		AUG	UST	SEPTEMBER.		
			Day Sec.ft		Sec.ft	Day	Sec.ft.	
Day 30	4.30	i	4.30	1	0.50			
		8	4.10	6	0.50			
		10	4.10	10	0.50			
		15	1.00					
		16	1.00	"o wate	r taken	after Aug.	10th.	
		19	1.00					
		23	1.00					
		31	0.50					

** Rasmus Larsen claims to irrigate 200 acres from the above 3 camals (w=18-a-b-c-), the acreage under each being unknown.

特格特特特特特特特特特特特特特特特特特特特特特特特特特特特

Diversion No.19-a.

WILLIAM LEMON CANAL NO.1.

Measuring Device............Good weir properly located. approximate Acreage......Unknown.

		Measur		in 1914.	CHAMBIARTE		
JUNE	J	ULY	AU	JGUST	SEPTEMBER.		
Day Sec.ft	Day	Sec.ft	Day	Sec.ft.	Day Sec.ft.		
	1	1.00	ì	1.40			
	3	0.96	6	1.90			
	8	0.00	9	1.40			
	10	0.00	12	1.30	No water diverted af-		
	15	0.00	15	1.40			
	16	0.00	19	1.30	ter Aug. 22nd.		
	19	1.30	22	1.30			
	23	0.40					

计转转转转计计符符转转转转转转转转转转转转转转转转转

Diversion No. 19-b. WILLIAM LEMON CANAL NO. 2.

"easuring Device.......Good weir properly located. Approximate Acreage......Unknown.

Measurements in 1914.

JUNE		JULY		A.	UGUST	SEPTEMBER.		
Day	Sec.ft.	Day	Sec.ft	Day	Sec. ft	Day	Sec.ft.	
30	1.00	1	2.50	1	0.00	1	0.40	
		3	0.00	6	0.00	4	0.00	
		8	0.00	9	0.20	7	0.00	
		10	0.60	13	0.00	9	0.00	
		1.5	0.00	16	9.00	13	1.40	
		16	0.00	19	0.00			
		19	0.00	22	0.00			
		23	0.00	25	0.00			
		31	1.40	28	0.00			
				30	0.00			

William Lemon Claims to irrigate 200 acres from the above 2 canals 9 (w-19-a-b-), the acreage under each being unknown,

Diversion No. w-20.

LARSEN AND BATES CANAL.

Measuring Device........................Good weir properly located.

Measurements in 1914.

J	UNE	JU	LY	1	AUGUST	SI	EPTEMBER.
Day	Sec.ft.	Day	Sec.fy	Day	Sec.ft	Day	Sec.ft.
11	4.20	1	1.20	i	1.70	i	0.30
19	2.00	3	1.10	6	1.00	7	1.00
24	1.60	8	2.20	9	0.60	10	1.00
27	0.90	10	1.10	13	0.50	13	0.60
28	1.80	15	1.60	16	0.30		
30	1.40	16	1.10	20	0.30		
		19	0.00	22	0.70		
		23	0.40	25	0.50		
		31	1.70	28	0.50		
				31	0.20		

Diversion No. 21-a.

JACK BATES CANAL NO1.

Measuring Device............Good weir properly located. Approximate Acreage.......Unknown.

JUNEN	J	ULY	AUG	UST	SEP	rember.
Day Sec.ft. 30 1.70	Day 1 3	Sec. ft. 1.70 1.70	Day 1 6	Sec .ft 0.00 0.00	Day	Sec.ft.
	7 10 14	0.00 1.30 1.60 1.70	9 12 15	0.00		
	16 19 23	0.00	19 22 25 28	0.00 0.00 0.00		
	31	0.00	31	1.10		

Diversion No. 21-b Jack Bates Canal No. 2.

Measurements in 1914.

JUNE	JULY		A	UGUST	SEPTEMBER.
Day Sec.ft.	Day	Sec.ft.	Day	Sec.ft.	Day Sec.ft.
30 5.00	4	4.70	1	0.00	
		1.50	6	0.00	
	7	0.00	9	0.00	
	10	0.00	13	0.00	No water diverted
	14	0.00	17	0.00	
	16	2.20	19	0.00	after Aug. 27th.
	19	1.40	21	1.70	
	23	1.50	24	1.60	
	31	0.00	27	1.60	
			31	0.00	
	****	*****	***	***	

Diversion No.21-c.

JACK BATES CANAL NO 3.

Neasurements in 1914.

JUNE		Jt	JLY	Al	AUGUST		SEPTEMBER.
Day	Sec.ft	Day	Sec.ft	Day	Sec.ft	Day	Sec. ft.
30	4.80	3	4.50	1	0.00	4	0.60
			1.30	7	0.00	8	0.50
		7	0.00	10	0.00	10	0.50
		10	0.00	13	0.00	13	0.00
		14	0.00	17	1.80		
		16	0.00	20	1.80		
		19	0.00	22	0.00		
		23	0.00	25	0.00		
		31	0.00	28	0.00		
				31	0.00		
		44 46 46 46 46 46 46	********	***	****		

Diversion No.21-d. KACK BATES CANAL NO 4.

Measuring Device...... Good weir properly located. Approximate Acreage........Unknown.

Measurements in 1914.

JUNE	JULY	AUGUST	SEPTEMBER.	
Day Sec.ft. 30 0.00	Day Sec.ft 3 2.20 7 0.00	Day Sec.ft	Day Sec.ft.	
	10 0.00 14 0.00 16 0.00	Measurements u	p to Sept. L3 show	
	19 0.00 23 0.00 31 0.00	no water diver	ted after July 3rd.	

特种转转转移移移移移移移移移移移移移移移移移移移移移移移移移移移移

Jack Bates Claims to irrigate 90 acres from the above 4 canals (w-21-a-b-c-d-), the acreage under each being unknown.

Diversion No.w-22.

HAROLD C. BEST CANAL.

Measurements in 1914.

JU	NE	JU	LY	AUGUAR	CEDMENT
Day	Sec.ft.	Day 3	Sec.ft 1.00	Day Sec.ft	SEPTEMBER. Day Sec. ft.
		8 10 15	1.00 0.30 0.30	Measurement	s up to Sept. 13 show no
		16 19	0.30	water dive	rted after July 23rd.
		23	0.30		
		31	00.00 ******	计林桥特特特特特特特特特特特特特特	****

Diversion No.23.w. UTAH POWER AND LIGHT COMPANY, POWER.

Measuring Device.........Good weir in tail race.
Approximate Acreage......water used to develop power at the Murdock Plant.

Measurements in 1914.

				THE RESERVE THE PERSON NAMED IN	The same of the sa		
JUNE			JULY		AUGUST		EPTEMBER.
Day 13 16 17 19 24 27 28 30	Sec.ft. 65.70 76.20 99.90 81.60 80.10 62.80 85.40 80.10	Day 2 6 9 13 15 16 19 20 22 26 27 29	Sec.ft 68.70 42.30 59.80 40.70 47.40 45.20 70.40 51.90 81.60 97.00 97.90	Day 5 6 8 9 11 12 15 18 21 24 25 28 31	Sec.ft 98.80 99.70 98.80 99.70 98.80 99.70 79.90 68.70 50.40 51.20 50.40 51.90 55.80	Day 1 2 4 7 10	Sec. ft. 51.90 55.80 63.80 63.80 56.60
			The state of the s	11 11 11 11 11 11 11 11 11	コモフビフビラビラビラビルドがおおおおおか	the first of the white with the district	

Diversion No. w=23-a.

UTAH POWER AND LIGHT COMPANY, IRRIGATION.

Measurements in 1914.

JUNE Day Sec. ft.	JULY Day Sec.ft 3 0.60	AUGUST SEPTEMBER. Day Sec. ft.
	7 1.00 9 1.00 14 1.00 16 1.00 19 0.50 23 0.60 31 1.00	Measurements up to Sept. 13 show no water diverted after July 31st.

Diversion No.W-24.

W.H. WALKER CANAL.

Measuring Device "one. Approximate Acreage Unknown.

Measurements in1914.

	JUNE	JULY		AU	GUST	SEPTE	MBER?
Day	Sec.ft	Day	Sec. ft.	Day	Sec. ft.	Day	Sec.ft.
		1 7	1.00				
		3	0.60				
		7	1.20	Mea	suerments up	to Sent.	1.3
		9	1.00				
		14	1.00	show n	o water diver	ted afte	n July 31
		16	1.00				coury or.
		19	0.60				
		23	0.60				
		31	1.00				
		****	****	****	****		

Diversion No.W-25

GEORGE DAVIS CANAL.

Measurements in 1914.

JUNE	J	JULY		AUGUST		EMBER?
Day Sec.ft.	Day 3 7 9 14 16 19 23	Sec. ft. 0.70 0.00 0.00 1.80 0.60 0.70 0.00	Day 1 7 10	Sec. ft. 0.00 0.00 0.00	Day	Sec. ft.
			****	********	1-11	

Diversion No.W-26.

LEVI NORTH CANAL.

JUN	В	JU.	LY	AUGI	JST	SEP	TEMBER.
Day 24 27 28 30	Sec.ft 1.10 1.10 1.10 0.80	Day 3 7 9 14 16 19 23 31	Sec.ft 0.70 0.70 1.70 0.60 0.60 0.60 0.60 0.60	Day 1 7 10 13 16 19 22 25 28 31	Sec. ft	Day 1 7 10 13	Sec. ft. 0.20 0.30 0.30 0.20
			- A HAM		THE RESERVE AS	******	

Diversion No. W-27.

JOHN BUTTERY CANAL.

Measuring Device............Good weir properly located. approximate Acreage.........50 acs.

Measurements in 1914.

JUNE		AUGUST			SEPTEMBER.	
Day Sec. ft	JULY Dat 3 7 9 14 16 19 23 31	Sec. ft. 1.50 1.50 0.70 1.10 1.10 0.50 1.20 0.50		Sec. ft. 0.50 0.30 0.20 0.10 0.20 0.80 0.80 0.80 0.90	Day 1 7 10 13	Sec. ft. 0.40 0.60 0.60 0.60
			31	0.40		
	**	***	****	************	*****	

Diversion No. W-28.

GBORGE DAVIS CANAL.

Measurements in 1914.

JUNE	JULY		AUGUST		SEPTEMBER.	
Day Sec.ft.	Day 1 3 7 9 14 16 19 23 31	Sec. ft. 2.00 2.40 0.00 0.00 0.00 0.20 0.00 0.00	Day 1 7 10 14 17 20 22 25 28 31	Sec. ft. 0.50 0.40 0.40 0.00 0.00 0.00 0.00 0.0	Day 1 7 10 13	Sec.ft. 2.40 1.80 2.00 2.40
		外种特殊特殊特种特种特种	अंदर करेंग कर कर की की की के के	I was all all all the city all all all all all all a	£ 36 36 36 36 36	

Diversion No.w-29.

JOSEPH MORRIS CANAL.

	NE		JULY	A	UGUST	S. W	PTEMBER.
Day 11	Sec.ft. 19.90	Day 1 3 7 9 14 16 19 23	Sec. ft. 5.00 6.00 4.00 3.60 3.30 1.00 0.20 2.00	Day 1 13 16 19 22 25 28 31	Sec. ft. 2.30 0.20 0.20 0.00 0.00 0.00 0.30 0.00 0.0	Day 1 7 10 13	Sec. ft. 0.30 0.30 0.30 0.30
			计计特特计计计标案	36 36 36 36 36 36 36 36 3	***********	***	

Diversiom No. w-30-a-b-.

THOMAS LAWRY ET AL CANAL.

Measuring Device.......weir, not properly located . Approximate Acreage......60. acres.

Measurements in 1914.

JUNE		JULY		Aligusm	CT	Daniel
Day Sec.	ft. Day 1 3 7 9 14	Sec. ft. 4.50 4.00 2.00 2.00 1.50	Day 1 7 10 13 16	AUGUST Sec. ft. 0.50 0.00 0.00 0.00	Day 1 7 10 13	FTEMBER. Sec. ft. 0.50 0.00 0.50 0.50 0.00
	16 19 23 31	0 .70 1.00 0.70 0.00 0.50	19 22 25 28 31	0.50 0.50 0.50 0.40 0.50		

特种特种特特特特特特特特特特特特特特特特特特特特特特特特特特特特特特

Diversion No. W31.

TIMPANOGAS IRRIGATION COMPANY.

Measurements in 1914.

JUNE	JULY		AUE	BUST	SE	PTEMBER?
Day Sec. ft. 12 58.80 13 62.30 23 61.70 24 62.30 27 60.60 28 60.60 30 61.70	Day 2 7 9 14 16 19 23 31	Sec.ft. 50.00 57.60 54.40 46.80 44.00 35.20 35.00 42.50	Day 1 7 10	Sec,ft. 42.50 40.30 38.70	Day	Sec. ft.

棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒

Diversion No.W-33.

GEORGE JORDAN ET AL CANAL.

JUNE Day Sec. ft.	JUI			UGUST	SEP	TEMBER.
Day Sec. ft.	Day 1 3 7 9 14 16 19	Sec. ft. 7.00 6.00 8.20 4.20 1.50 2.40 2.70 3.20 1.60 2.60 1.90	Day 1 7 10 13 16 19 22 25 28 31	Sec. ft. 1.90 0.60 1.80 1.80 1.30 0.60 0/50 2.50 2.60 0.00	Day	Sec. ft.

Diversion No.W-34.

ISAAC R. BAUM CANAL.

Measuring Device...........None.
Approximate Acreage......100 acs.

Measuerments in 1914.

JUNE	JULY	Δ	UGUST	
Day Sec.ft.	Day Sec. 8 1. 10 1. 14 1. 16 1. 19 0. 23 0. 31 0.	ft. Day 50 16 50 19 50 22 00 25 80 28 70 31	Sec. ft. 0.80 0.50 0.50 1.60 0.00 0.80	SEPTEMBER. Day Sec.ft.

Diversion No.W-35.

WASATCH IRRIGATION COMPANY.

TERRICATION COMPA NORTH FIELD IRRIGATION COMPANY AND OTHERS.

Measurements in 1914.

				THE REAL PROPERTY.	TRAIN THE		
Day 12 30	JUNE Sec.ft 204.10 170.00	Day 1 7 9 14 16 19 23	Sec. ft. 180.00 153.00 160.00 150.00 123.00 112.00 160.00 124.00	Day 1 7 10 13 16 20 25 28	AUGUST Sec. ft. 122.00 122.00 112.00 111.0 114.50 97.00 85.60 95.50 72.40	SE Day 1 2 7 10 13	PTEMBER. 560. ft. 75.50 74.60 56.90 50.30 56.50

特赖特特特特特特特特特特特特特特特特特特特特特特特特特特特特特特特特特特

MEASUREMENTS OF FLOW

OF

WATER FROM ONTARIO DRAIN TUNNEL 1914.

Gaging Station located at County Road crossing of Tunnel Creek near its confluence with the Provo River. Measurements made and reported by Deputy Commissioner, George F. Taylor.

	UNE	JUI	Y	AUC	SUST	SEPTI	EMBER.
Day	Sec.ft.	Day	Sec.ft.	Day	Sec.ft.	Day	Sec.ft.
11 13 16 17 19 23 24 27 28 30	19.80 17.80 17.50 17.30 17.30 15.90 17.30 16.70 17.30	1 3 6 7 10 14 16 17 19 20 21 23 27 28 29	14.70 16.70 17.30 18.60 17.30 17.80 17.30 17.30 20.30 20.30 20.30 18.40 17.80 17.80 17.80 18.40	5 6 8 9 11 12 15 18 21 24 25 26 28 30	18.10 18.40 18.40 18.40 17.50 17.30 17.80 18.10 17.50 18.60 18.60 18.60 18.60	1 4 5 7 10 14	18.40 18.40 18.40 18.40 17.80

Of the total flow of Tunnel Creek, 5.50 Sec.ft. was turned to the Midway Irrigation Company and the balance to the Provo Reservoir Company.

8

THE UNION RESERVOIRS.

The reservoir system of the Union Reservoir Company consists of three comparatively large lake-reservoirs, namely: Washington Lake Reservoir, Trial Lake Reservoir and Wall Lake Reservoir, and thirteen smaller reservoirs, all of which are tributary to the three named above. These lakes are made to serve as reservoirs by placing dams across the outlet channels and providing gates with which to regulate the flow therefrom.

The out-flow from all of these reservoirs unites in a common channel some distance below Trial Lake outlet. The stream was measured in this channel during 1914 by means of a gaging station ni the natural s solid rock channel, about 2000 feet below the outlet from Trial Lake Reservoir. This station is very unsatisfactory for the proper measurement of the flow, on account of the high velocity and on account of the difficulty of reading the gage properly due to the rough water surface. When the flow exceeds 50 second-feet, a difference in gage height of 0.01 ft. makes a corresponding difference in discharge of approximately 9 second-feet, and since it is very difficult to read the gage even to the nearest 0.01 ft., the measurements could very easily be in error 5 second feet at this stage.

During the year 1914, daily gage readings were taken at this station by George A. Clift r. from July 15th to Sept. 4th, the period during w which storage water was being drawn. A rating curve was compiled for the station from 5 measurements made by I.H. Jacob, 7 measurements made by Frank W. Deming and 1 measurement made by George F. Taylor. This curve was used to determine the daily discharege as reported herein.

The natural out-flow was measured by your Commissioner on July 17th and found to be 4.20 second-feet. On August 26th, an estimate of the inflow to these reservoirs was made by C.S.Jarvis, Engineer for the Company, who placed it at 2.10 second-feet. The average of these two determinations or 3.15 second-feet was taken as the average natural out-flow for the period during which the storage was being released.

A copy of the daily discharge in second-feet and the quantities in acre-feet is attached hereto, also an estimate of the total storage for the year 1914.

Un.Res.(20):

These data show a total storage of 4361 acre-feet, which, according to the Secretary of the Company, is divided among the various companies in interest as follows:

Wasatch Irrigation Company 7/28..... 1090 ac.ft/
Timpanogas Irrigation Company 7/28......1090 " "

Sego Irrigation Company

Provo Reservoir Company.

In addition to the 12/28 interest in the storage of the Union Reservoir Company, noted above, the Provo Reservoir Company operates three systems of smaller reservoirs known as (1) The North Fork System, (2) The Lost Lake System, and (3) The Haystack System.

2/28

12/28

..... 310 "

..... 1870 "

On account of there being no suitable measuring devices in the various outlet channels, no reliable data on the outflow from these reservoirs were obtained during 1914. A series of measurements made at the two stations on the North Fork System, extending over the period from July 16th to August 13th gives the following data on outflow: Average flow from July 16th to August 2nd, at which latter time the storage was released, 4.14 second-feet. Average floe from August 2nd to August 13th, 12.60 second-feet. These measurements reduced to acrefeet are given below-

The following table gives the total storage of the Provo Reservoir Company as shown by the best available data; the available storage in the Lost Lake and Haystack Systems being taken from the report of C.S.Jarvis, Engineer.

Total Storage for the year 1914..... 2313 ac.ft.

Due to the inaccuracies in measurements noted above, these totals of the Union Reservoir Company and The Provo Reservoir Company may be considerably in error, however, these are the best available data, till proper measuring devices are installed ehich should be done before the water is released this year.

MEASUREMENTS OF

THE FLOW OF WATER FROM THE RESERVOIRS OF THE UNION RESERVOIR COMPANY.

1914.

Gaging Station Located about 2000 feet below the outlet from Trial Lake Reservoir . Measures all of the stored water of the Union Reservoir Company, including natural out-flow.

Gage Readings By George A.Clift Jr. Computations By Frank W.Deming.

Day Secc.ft. Ac.ft.	Day	AUGUST Sec.ft.	Acft.	SE	PTEMBER. Sec.ft.	Acft.
			*****		****	
15 4.70 9.40 16 4.70 9.40 17 5.50 11.00 18 9.50 19.00 19 13.50 27.00 20 38.50 77.00 21 36.50 73.00 22 38.50 77.00 23 38.50 77.00 24 40.50 81.00 25 43.00 86.00 26 43.00 86.00 27 43.00 86.00 28 67.00 134.00 29 67.00 134.00	1 2 3 4 5 6 7 8 9 10 11 12 15 14	67.00 67.00 43.00 48.00 52.50 57.50 67.00 67.00 43.00 43.00 43.00 43.00 45.50 67.00	134.00 134.00 86.00 96.00 105.00 115.00 134.00 134.00 86.00 86.00 86.00 91.00 134.00	1 2 3 4 To	28.50 28.50 16.00 7.00	57.00 57.00 32.00 14.00
30 67.00 134.00 31 67.00 134.00 Total 1253.00 atural out-flow July 74.20 s.ft.	16 17 18 19 20 21	67.00 67.00 67.00 67.00 67.00 50.00	134.00 134.00 134.00 134.00 134.00 100.00			
atural inflow Aug.26	22 23 24 25	52.50 52.50 52.50 52.50	105.00 105.00 105.00			
verage for the period f 51 das3.15 s.ft.	26 27 28 29 30 31	52.50 52.50 52.50 28.50 28.50 28.50	105.00 105.00 57.00 57.00 57.00 57.00 3269.00			
Total in Acre-feet Estimated natural of 3.15 sec.ft.for 51 Total Sto	das	w for the	e period		321.00) An Ct

REPORT OF

DEPUTY COMMISSIONER, C.F. TAYLOR.

特特特特特特特特特特特特特特特特特特特特特特特特特

Provo, Utah, Sept.11,1914.

Mr. Frank W. Deming,

Provo, Utah.

Dear Sir: -

At your request, I am reporting the conditions and recommendations on the canals and ditches in the upper division of the Provo River.

The water at the Wasatch Dam has been diverted from the River into the canal by means of flash boards during the season. These boards were not even nailed or fastened. They warp and draw out of place: thus allowing more or less water to pass through and causing the flow passing the dam to vary. They can stop the greater part of the water leaking through the flash boards by nailing them and placing a canvas in front of them

The Wasatch, North Field nad Charleston Canals Have not a suitable measuring devote. They should have a weir or rating flume and an automatic register to give the flow in their canals. The automatic register is necessary because the canals are below the two power plants and they cause the water to fluctuate in the river below.

The Isaac R. Baum ditches have no measuring devices, but weirs or rating flumes can be placed in them.

The Timpanogas Canal has a good rating flume and no change is necessary.

The Heber Power P ant has no measuring device. They have a good place to put in a weir and it should be built so as to have an automatic register. Their flume is in very poor shape, allowing as much as ten second -feet to leak out and pass down into fields or pastures below to the road where a part is used for irrigation purposes by the farmers. Something should be done to prevent this water from being used by those who have no right to it and also to get it back into the River or canal below. The best thing to do would be to repair the flume. It is not possible to prevent some water from leaking through the flume; but a right of way and ditch should be had to convey the water to the river or canal after it gets out of the flume.

The George Jordan ditch has a good weir but it is too far from the head gate and require too much time to regulate it. Aweir should be placed near the head gate.

The Lawry Ditches have not suitable measuring devices. The weir was placed so as to measure the total flow from the spring and also from the river. A weir should be placed in each ditch if possible. The channel from the river is large and it may not be possible to locate a place where a weir would stay during high water.

The main Morris ditch has a good rating flume properly located.

There are two other Morris ditches and they have no measuring devices.

They seldom use these two ditches. One of them was not used this year taht I know of. The other one was used about three times. Weirs or rating flumes should be placed in them foe another year.

The Davis Brothers have a small ditch which heads in the channel conveying the Tunnel water. It should have a small weir.

The Davis ditch which gets water from the river should have a rating flume or a weir near its head. I used the flume over the tail race at the Murdock Power Plant this year; but it is too far from the head of the ditch and some land is irrigated above this flume.

The channel conveying the Tunnel water has no measuring device. A weir or rating flume should be installed before another season in order to tell how much water is added to the river from this stream. A weir would be better than a rating flume wherever it can be properly placed. There is plenty of fall and also a good place for a weir just below the point where the Morris ditch heads.

The John Buttery ditch has a good weir.

The Levi North ditch has a good weir.

The George Davis ditches have no measuring devices as they were n not used to speak of except during high water this year when the water was too high to put in weirs.

The W.H. Walker ditch has no measuring device; but it should have a weir. The same is true of the Utah P wer and Light ditch.

The Harold C. Best ditches have no measuring devices as they only drew water during high water. The river cut a new channel around the head of these ditches and made it expensive to make a dam high enough to turn water into these ditches. They should have weirs for another year.

The four ditches belonging to John Bates all have good measuring devices properly located.

The William Lemon ditches have good weirs properly located.

The Rasmus Larsen Ditches have good weirs properly located.

The Ola W. Larsen ditches have good weirs properly located.

The James A.Knight ditches #13 and #16 have good weirs properly located.

The James A. Knight ditch #17 has no measuring device. It is only used for high water and the water would flow over on all sides of the weir and head gate.

The Ether Webb ditches ,#15-a and #15-b have good weirs properly located. The Ether Webb ditch from Webb Creek has no measuring devoce. It should have a weir.

The Turnbow and Gines ditch has a good rating flume properly located.

The Cutler ditch has a good rating flume properly located. The Nephi and William Moon ditch has a good weir properly located. The FItzgerald and Hardman ditch has a good rating flume proper ly located.

The (Upper) moon ditch has a good weir properly located.

The Thomas White ditches have no measuring devices. They have not used water except high water.

The Phillips ditcher has six branches; but two are headed at the same place and one weir will do for these two. There are five weirs in this system. Some 66 of them could be lowered and it would help cases; because as there are at present the water has to be backed up in the Washington Canal in order to pass over the weirs. The one used the most is properly located.

The Washington Canal has a good rating flume properly located, Exceptive that the textile water temperating themse this canal has a poor head gate and the dam is also in a bad shape.

They need a better head gate and dam in order for the water commissioner or any one else to regulate the water in the canal.

The South Kamas has a good rating flume properly located, except that there is water seeping out of the canal below the rating flume which flows directly into the Washington Canal above its rating flume where it is measured again. It would be more just for the owners under the South Kamas Canalto have their rating flume moved down the canal even with that of the Washington, or better still have both rating flumes put on top of the bench; because the water that seeps through the lower bank of these canals

The J.M.Duncan ditch has a good weir properly located. This ditch has a very small stream all season which is claimed for culinary and domestic purposes.

gets into the spring creek below the hill and is conveyed to the river.

The Stewart Brothers ditch #3 has no measuring device; it should have a rating flume as it has not fall enough for a weir.

The Sunrise Canal has a goog rating flume properly located.

The Stewart Brothers four ditches #1-a-b-c & d all have good measuring devices.

I would recommend a trapezoidal weir in all cases where the conditions are suitable for a weir of that kind. The farmers can learn to measure the water over the crest of the weir and know for themselves what their ditch is drawing.

The Eurdock Power Plant has two good rectangular weirs which are located just below the power plant. The men at the plant keep a record of the water passing through the plant.

The Utah Power and Light Has established a gaging station about one half mile below their diverting dam. (This is the diverting dam of the Murdock Plant) This station is for the purpose of finding out how much water passes over their dam.

A gage is located at what is known as Best's Bridge on the Provo River. This station is about one mile above the Utah Power and Light dam This gage has been red during this season.

There is not a suitable measuring device at any of the lakes or reservoirs. We had to take ratings in the channels. Some 66 of the channels were so rough and rocky that a good place could not be found. In most every case the conditions were in favor of a weir and I would recommend that weirs be placed with an automatic gage at each weir. That will only require two of the gages as one can be used for the small lakes and moved to another weir as soon as the water has been drawn out.

These gages are necessary to figure out how much water flows from the lakes.

The lakes are so located that it seems to me that a water commissioner s hould be placed in the field where he could measure the streams at various places and figure the losses RE XX in transporting the water from the lakes to the river. There is enough work at the lakes to keep one man buisy in keeping track of the water from the lakes. I would recommend that a water commissioner be appointed to stay at the lakes and get such information as is needed in order to know how much water is turned from the lakes to the River.

The water from the Big Elk (Washington Irrigation Co.) Lake or reservoir passes over what is called Dry Lake and then flows through a narrow channel. A rating station was meade and a gage placed in this channel. The channel is not deep enough for a weir but a good rating flume can be built. An automatic gage should be placed so as to give the quantity of water flowing in the flume from the reservoir.

There was no lake or surface gage to read at the Big Elk Reservoir. I drove a nail in a large pine tree on a level with the surface of the water just above the dam. The Reservoir Company should place a gage so that the depth of water in the reservoir can be redd at any titime. This is necessary in order for the Water Commissioner to figure the capacity by knowing how much is flowing out or to check on the outflow by knowing the capacity 66 of the reservoir. The Company should also furnish a capacity table or curve for the Water Commissioner.

The Murdock Power Plant has done some repairing on their diverting dam at the head of their pipe line this season. They have fixed the dam so as to use flash boards and thus raise the water during the low water. These flash boards have not been properly used during the months of August and September of this year. By using the flash boards and allowing the water to spill over them into the channel below the flow ca can be held nearly constant. They have had one gate opened from the bottom letting water pass through and nothing spilling over, then when the pipe line drew more water, the water in the reservoir would lower and more than the natural flow of the river would go down for a while, until the flow in the pipe line decreased and then the water in the reservoir

would have to rise and less water would flow down the river than the natural flow of the river.

The Power Plant has by-passes which can be operated to keep the flow constant whether they have the same power developed or not. The natural flow of the river can be held constant by allowing the water not passing into the pipe line to flow over the flash boards. This will keep the water above the dam nearlt constant and by operating the by-p passes properly the flow in the tail race can be kept constant. They have two good 8-ft. rectangular weirs inthe tail race just below the Power Plant and by reading the hook gage they get the depth flowing over the weirs.

The people in the Wasatch Division do not have the same "duty of water" in all sections. During the high water season they use much more water per acre than when the water is low. Some of the people use a second foot to about 25 or 30 acres in high water and others do not use as much. During the extra high water season a duty of one secondfoot for 30 or 35 acres for the Wasatch Division is about what was used this season

The people cannot irrigate one half of their land with the water given them in the Fulton Decree. Some have not enough water to keep their ditches wet. By watering in turns or rotation, keeping the stream above one second-foot, they can irrigate to better advantage.

Yours Respectfully,

(Signed) Goorge F, Taylor.

DUTY OF WATER.

Tere are no reliable data available on the "duty of water" on the lands irrigated from the Provo River. The manner of use and quantity of water used has been established by the users generally upon the theory that the crop production varies directly with the quantity of water used at all times. This may or may not be true. Various experiments in this and other arid states demonstrate that there is a certain duty in screfeet per acre, depending upon the soil, and climate, and crops, which is most desirable and economical for any particular district. The manner of application, time of application and various other factors enter into this determination.

Since no experiments along this line have ever been condutded in any of the districts served by the Provo River; and since the proper determination of the rights involved in this cause depends upon the duty of water under the various conditions of soil and climate, your Commissioner espectly recommends that such a series of experiments be authorized and ordered.

This could very nicely be done seperately from the distribution of the waters of the River, by competent, disinterested parties, and in such a proper and thorough manner that the question of "duty" on the lands irrigated by the Provo River would be settled for all time on the proper basis, which is that of crop production per unit of water per acre. This duty, of course would be applicable only during the high and intermediate stages of the River; since below the stage at which there is sufficient water for all the users, the question of priority of right enters in. This question, however, is fairly well determined by Court Decrees and by recognized rights among the users themselves.

The cost of such an investigation would be comparatively great, but in the opinion of your Commissioner, would decrease the total cost in this otherwise cause, and possibly inothers that might arise in the future, by avoiding costly and possibly endless litigation.

Valuable assistance along this line could probably be obtained from the Office of the State Engineer and the State Agricultural College.

Pending such a proper determination of duty, your Commissioner recommends that a temporary agreement or stipulation be entered into by
the various parties to this action, defining the duty in the several dis-

tricts, for the guidance of the Court Commissioner in making proper distribution during the period of high and intermediate stages of the River.

During the year 1914, your Commissioner obtained a fairly complete record of the flow of water in 14 of the larger canals of the Provo River er system, from which the duty during the year in acre-feet per acre and in acres per second foot of water was computed; in most cases based upon an estimated acreage. The monthly and yearly maximum, minimum and mean duties for the Provo and Wasatch Districts and for the entire River are also computed. Since these measurements extend only over the period of ser vice of your Commissioner and Deputies (from June 1st to September 1sth) they do not show the total quantities ofwater used during the irrigation season. Copies of these data are attached to and made a part of t this report.

The question of 2 "duty" confronted your Commissioner during the year 1914, in the matter of the complaint of the Provo Bench Canal and Irrigation Company, Defendant; and the subsequent appeal to your Honor by the Provo Reservoir Company, Blaintiff. In order to determine the question in the best manner, under the circumstances, and for the lack of any data on the duty on Provo Bench, an attempt was made, before and after said appeal, to determine the depth of water applied to the land at each irrigation, on the various kinds of soil; and from the testimony of the users as to the required frequency of irrigations at that time of the year, calculate the required duty in acres per second-foot. A copy of these data are attached to and made a part hereof.

These data submitted herewith show considerable difference rate of use of water and in total water applied to the land, under the various systems, indicating, probably a difference in customary usage as well as a difference in requirements; but since no data were obtained on crop production nor methods of use, it is impossible to make comparisons as to benificial use.

Diversions Nos.w-1-a-b-c-d- & w-3.

STEWART RANCH COMPANY? WOODLAND.

5 Small Canals, diverting water directly from Provo River and irrrigating approximately 630 acres.

WATER DIVERTED IN 1914.

Month	Quantity acre-ft.	Depth on Land in ft.	Duty in Acs.per Sec.ft	Remarks

June	945	1.500	40.0	
July	482 156	0.765	81.0	
August	0-847	0.847	251.0	No water af-
Totals	1583	2.512	-	ter aug. 24

Average Duty for the year in acres per second foot, 69.0

Diversion No. w-2.

SUNRISE CANAL COMPANY? WOOD AND

One Canal diverting water directly from Provo River and from Bench Creek in the early part of the season, irrigating approximately 500 acres

WATER DIVERTED IN 1914.

Quantity acre-ft.	Depth on Land in ft.	Duty in acs.per	k _{emarks}
660	1.320	45.4	
541	1.082	57.3	
311	0.622	99.7	
80	0.160	190.0	
1592	3.184		
	acre-ft. 660 541 311 80	acre-ft. Land in ft. 660 1.320 541 1.082 311 0.622 80 0.160	acre-ft. Land in ft. acs.per 660 1.320 45.4 541 1.082 57.3 311 0.622 99.7 80 0.160 190.0

Average duty for the year in acres per second foot, 67.3

Diversion No.w-5.

SOUTH KAMAS IRRIGATION COMPANY, KAMAS?

One canal diverting water directly from Provo River and irrigating approximately 1700 acres.

WATER DIVERTED IN 1914

Month	Quantity acre-ft	Depth on Landin ft.	Duty in Acs. per sec Remarks
June	2205	1.297	46.2
July	2033	1.196	51.6
August	1568	0.922	67.3
Sept. (15 das.)	411	0.242	124.0
Totals	6217	3.657	

Average duty in acres per second foot for the year, 58.5

Diversion NO.w-6.

WASHINGTON IRRIGATION COMPANY KAMAS.

One canal diverting water directly from Provo River and irrigating approximately 1200 acres.

WATER DIVERTED IN 1914.

Month	Quantity acre-ft.	Depth on Land ft.	Duty in acs. per se	c.Remarks
June	1222	1.018	59.0	
July	1192	0.993	62.4	
August	763	0.636	97.5	Stored water 385 ac.ft.
Sept.(15 das.)	121	0.101	299.0	
Totals	3298	2.748	XXXX	

Average duty for the year in acres per second foot, 77.8 acs.

Diversion No.W-31

TIMPANOGAS IRRIGATION C OMPANY, HEBER.

One canal diverting water directly from Provo River and irrigating approximately 2000 acres.

WATER DIVERTED IN1914.

Month	wuantity Acre-ft.	Depth on Land ft.	Duty in acs.per	Remarks.
June	3630	1.815	33.0	
July	2788	1.394	44.6	
August(10 das.)	817	0.408	49.0	
Totals	7236	3.617		

Average duty for the year in acres for second-foot, 39.7 acs.

经转移转移转移转移转移转移转移转移转移转移转移转移转移转移转移

Diversion No.W-35.

WASATCH IRRIGATION COMPANY, HEBER.

NORTH FIELD IRRIGATION COMPANY, HEBER.

EXTENSION IRRIGATION COMPANY, HEBER.

CHARLESTON IRRIGATION COMPANY, CHARLESTON.

SAGE BRUSH IRRIGATION COMPANY, HEBER.

The water is diverted directly from Provo River and is used mainly by the wasatchand North Field Companies. The other canals mentioned above are supplied principally by seepage and from Spring Creek. The combined acreage is approximately 7100 acres. The following data take into account only the water diverted directly from Provo River.

WATER DIVERTED IN1914.

Month	Quantity Acre-ft.	Depth on Land ft.	Duty in Acs.per sec. foot.	hemarks
June	11628	1.638	36.6	
July	9116	1.284	48.3	
August	6452	0.909	68.2	
Sept.(15 Das.)	1782	0.250	120.0	
Totals	28978	4.081		

Average duty for the year in acres per second-foot, 52.4 acres.

Diversion NO.P-100.

MIDWAY IRRIGATION COMPANY, MIDWAY.

At least 12 small canals diverting water from Provo River and Snake Creek and from Springs. Two divert from Provo River, two from springs and at least eight from Snake Creek. Om account of the large number of canals and lack of proper measuring devices, these data are rather approximate. Acreage approx. 4100 acs.

WATER	DIVERTED	IN	1914.
-------	----------	----	-------

Month	Quantity acre-ft.	Depth on Land in ft.	Duty in Acs.per se Foot	c.Remarks
June	6000	1.463	41.0	Approx.
July	4398	1.072	58.0	
August	2986	0.728	85.1	
ept. (15 das.)	650	0.160	187.5	
Totals	14034	3.422		

Average duty for the year in acres per second foot, 62.5 acs.

Diversion No. P-1.

PROVO RESERVOIR COMPANY PROVO

One canal diverting water directly from Provo River, and irrigating approximately 4800 acres.

WATER DIVERTED IN 1914.

Month	Quantity acre-ft.	Depth on Land ft.	Puty in Acs per sec Remarks ft.
June	5785	1.205	50.0
July	4579	0.954	65.0
August	4021	0.838	74.0
Sept. (15 das.)	1377	0.286	104.8
Totals	15762	3.283	

Average duty for the year ib acres per second foot,65.2 acs.

"iversion No.P-L-a.

SEGO IRRIGATION COMPANY, PROVO.

Tthe water used by this company is diverted thru the flume of the Utah Power and Light Company, and delivered to the land thru a pipe 7100 feet long which leads from the penstock of the Fower Company. The acreage irrigated is 200 acs.

WATER DIVERTED IN 1914.

Month	Quantity in acre-ft.	Depth on Land in ft.	Duty in Acs per sec Remarks ft.
May	* 335	1.675	37
une	324	1.620	37
July	226	1.130	55.0
August	176	0.880	70.4
Sept.(15 das.)	.72	0.360	83.3
Totals	1133	5.665	

Average duty for the year in acres pwr second-foot, 48.7

Diversion No. P-2.

TIMPANOGAS CANAL COMPANY, PROVO

One canal diverting water directly from Provo River, and irrigating approximately 900 acres.

WATER DIVERTED IN 1914.

Month	Quantity in acre-ft.	Depth on Land in ft.	Duty in Aos per sec.Remarks ft.		
June	1861	2.068	29.0		
July	1432	1.581	39.2		
August	1087	1.208	51.2		
Sept.(15 das.)	508-	0.564	53,2		
Totals	4879	5.441			

Average duty for the year in acres per second-foot, 39.3 acs.

^{*} Thw quantity used by this diversion during May was determined by determining the capacity of the pipe which was kept running full during this month. This makes the depth on the land 1.675 ft. greater for the year, compared with the other diversions.

Diversion No.p-3

PROVO BENCH CANAL AND IRRIGATION COMPANY RROVO

One canal diverting water directly from Provo River and irrigating 4332 acres.

WATER DIVERTED IN 1914.

Month	Quantity ACDD-ft.	Depth on Land ,ft.	Duty in acs.per sec.ft
June	7726	1.783	33.7
July	6101	1.408	44.0
August	5818	1.343	46.2
Sept.(15 Das)	2832	0.654	46.0
Totals	22477	5.188	

Average duty for the year in acres per second-foot, 41.2 acs.

Diversion No.P-4.

WEST UNION CANAL COMPANY ET AL

One canal diverting water disectly from Provo Piver and irrigating approximately 1900 acres.

WATER DIVERTED IN 1914.

Month	Quantity Acre-ft.	Depth on Land in ft.	Duty in Acres per Remarks Sec. ft.
Manihx June			0 '00' 100' 100' 100' 100' 100' 100' 10
	3347	1.761	34.1
July	2559	1.347	46.0
August	2325	1.224	50.8
Sept.(15 das.)	1087	0.672	52.6
Totals	9318	4.904	With the Control of t

Average duty for the year in acres per second-foot, 43.6 acs.

EAST RIVER BOTTOMS WATER COMPANY.
AND ALL USERS OF WATER IN THE EAST RIVER BOTTOMS.

Seventeen (17) small canals diverting water from City Creek. The acreage irrigated by these canals is very uncertain. The owners claim about 900 acres, while a survey made under the direction of the plaintiff in this case shows 516 acs. The following data are based on an acreage of 900.0

WATER DIVERTED IN 1914.

Month	Quantity Acre-ft.	Depth on Land in ft.	Duty in acs. per Remarks Sec.ft.		
June	2871	3.190	18.8		
July	1712	1.902	32.6		
August	1535	1.705	36.5		
Sept.(15 das.)	686	0.762	39.4		
Totals	6804	7.559			

Average duty for the year in acres per second-foot, 28.2 acs.

Diversion No. P-6.

TPPER EAST UNION CANAL COMPANY AND FAUCITT FIELD DITCH COMPANY, PROVO.

One canal diverting water directly from Provo River and irrigating approximately 900 acres.

WATER DIVERTED IN1914.

Month	Quantity Acre-ft.	Depth on Land in ft.	Duty in Acs.per Remarks. Sec. ft.
June	2078	2.309	26.1
July	1640	1.822	34.4
August	1444	1.604	38.8
Sept.(15 das.)	701	0.780	38.4
Totals	5863	6.515	

Average duty for the year in acres per second-foot, 32.8 acs.

SUMMARY OF DATA

ON THE USE OF WATER FROM PROVO RIVER FOR IRRIGATION

ro	vo Divis	sion. (7	canals): JUL	[-****** 开4开操**		JGUST	SEPTY	BMBER
Month	Dep. I	Dut.	Dep. I	out.	Dep.	Dut.	Dep.	Dut.
max.	3.190	18.8	1.902	32.6	1.705	36.5	0.780	38.4
Min.	1.205	50.0	0.954	65.0	0.838	74.0	0.286	104.8
Mean	1.991	30.1	1.449	42.8	1.257	49.3	0.568	53.0
Was	atch Div	vision.	(7 cans	als)				
'dax.	1.815	33.0	1.394	44.6	0.922	67.3	0.250	120.0
"in.	1.018	59.0	0.765	81.0	0.247	251.0	0.000	0.000
mean	1.247	48.1	0.958	64.7	0.550	112.7	0.107	280.4
		D.1	/24	0 - 1				
Ent	ire Pro	vo River	• (14	Canals)				
Max.	3.190	18.8	1.902	32.6	1.705	36.5	0.780	38.4
Min.	1.018	59.0	0.765	81.0	0.247	251.0	0.000	00.0
Mean	1.619	37.1	1.203	51.5	0.904	68.6	0.337	90.0

In the columns headed <u>Dep</u>, are given the maxima, minima, and mean depths on the land, or the quantity in scre-feet per acre for each month. In the columns headed <u>Dut</u>, are given the equivalent "duties" in acres per second-foot. The acreage in most cases is approximate as shown in the accompanying table of measurements. Since the acreage in most cases is probably in excess of the true values, the quantities who of water per acre as shown above are probably less than the true values.

These data are not submitted as indicating an economical "duty of water", but merely to show, as nearly as may be, the rate of use and quantities used.

The measurements from which the computations were made are submitted herewith, and will show, in a general way, the degree of accuracy which might be expected in each case.

8

ON

RROVO BENCH ******1914

ract No.1-John Stratton.

Arae- 3.53 Acres.
Soil-Sandy Coam.
Sub Soil- Gravelly
Crops-Truit trees & alfalfa.
Length- 603 feet
Width- 253 feet

July 26,1914.

Measurements of flow by Current meter.
Average Flow-9.15 sec.ft.
Time- 9:40 to 1:40..4 hrs.
Quantity of water in ac.ft
3.050
Depth on land-0.864 ft or
10.37 inches.

The tract was irrigated the long way, from East to West.

将兵会会转移的转移的特殊的特殊的特殊的特殊的特殊的特殊的特殊

Tract No.2- Arthur Marriot.

Area---1.90 acs.
Soil-Sandy loam about 3.5
to 10 fleet deep.
Subsoil- Gravelly.
Crops- Alfalfa
Length- 483 feet
Width- 171 Feet.

July 30,1914.

Measurements of flow by current mater.

Average Ebww.- 4.765 sec.ft.

Time-1:05 to 3:00 p.m.

1 hr. 55 min.

Quantity of water in acre-feet- 0.397

Depth on land-.4000 ft or 4.80 inches

The tract was irrigated the long way, from East to West.

Tract No.3-.....Crandall

Area-1025x 10.83 scres. Soil-Gravelly, clay loam. Sug soil- Gravel. Crop- Alfalfa. Slope- 1.75% to west. Length- 1255 feet Width- 376 feet August 10,1914.

Measurements of flow by
means of a 4-foot rectangular weir.
Average flow- 3.18 sec.ft.
Time- 7:15 a.m. to 8:15 p.m.
13 hours.
Quantity of water in acre-ft.
3.44
Depth on land-0.318 ft. or
3.82 inches.

The tract was irrigated the long way, from East to West. At 4:10 p.m. there was approximately 8.00 acres irrigated. 3:18 sec ft. for 9 hours equals 2.385 ac.ft. or a depth 2.98 ft. over 8.00 acres.

Tract No.4.- Barney Biglow.

Area--9.63 acres.
Soil- Gravelly Clay Loam.
Sub Soil- Gravel.
Crops- Alfalfa & Fruit.
Slope- 1% to South.
Length- 662 feet
Width- 632 feet.

August 11,1914.
Measurements of flow by
means of 3-ft. submerged
weir.
Average flow- 3.96 sec.ft.
Time-7:15 s.m. to 4:00 p.m.
8 hrs. 45 min.
Quantity of water in screft. 2.90
Depth on land-0.301 ft or
3.61 inches.

This tract was irrigated the long way, from North to South.

Tract No.5 .- James A. Loveless.

Area- 7.52 acres.
Soil- Gravelly Clay loam.
Sub Soil- Gravel.
Crpps- Alfalfa and Fruit.
Slope- 0.7% to South.
Length- 1300 feet.
Width- 250 feet.
Measuerments of flow by current meter.
Average flow- 7.86 sec.ft

August 11,1914

Time- 9:00 a.m. to 2:00 p.m.- 5.00 hrs. Quantity of water in acrefeet- 3.276 Depth on land- 0.435 ft.or 5.22 inches.

At 11:00 ga.m.there was approximately 4.70 acres irrigated. 7.86 sec.ft for 2 hrs is 1.31 acre-feet, or a depth on the land of 0.28 ft. or3.36 inches.

촦촦춖뽂쯗춖춖똮똮춖쯗춖놖똮쯗똮똮똮똮

Tract No.6 .- W.A. Marriot.

August 22,1914.

Area--- 4.08 acres
Soil- Sandy loam.
Sub Soil- Gravel.
Crops- Fruit trees and alfalfa.
Length 686 feet.
Width- 259 feet.
Measurements of flow
by current meter.

Average flow- 3.87 sec.ft. Time-1:30 P.M. to 6:00 p.m. equals $4\frac{1}{9}$ hrs. Quantity of water inacrefet 1.42 acre-ft. Depth on alnd-0.348 ft. or 4.18 inches.

The irrigation of this tract was thorough. Some water ran off at the lower end on account of imperfext regulation. This was estimated at 0.07 ac.ft. and is deducted from the t total water applied. From evidence in a three-foot hole the water had reached a depth of 2 feet, 3 hours after its application.

Tract No.7 .- William Downs.

Arae- 2.35 acres.
Soil- Gravelly 'lay lowm.
Sub Soil- Gravel.
Crops- Fruit trees, strawberries and raspberries.
Length- 396 feet.
Width- 246 feet.Also a tract
50x100 feet at the west end.

Measurement of flow by current meter.
Average flow- 3.30 sec.ft.
Time-1;00 p.m. to 2:30 p.
m. 1 hours.
Quantity of water inacrefeet- 0.412.
Depth on land-0.175 ft.or
2.00 inches.

The irrigation of this tract was fair, the slightly irregular. There was a small quantity of water ran off, while implaces it did not run through the length of the tract. The irrigation was by the furrow method, there being 5 furrows between the rows of trees.

Tract No.8 .- Newell J. Knight.

August 25,1914.

Area-1.71 acres.
Soil- Sandy, Cravelly loam.
Sub Soil- Gravelly.
Crops- Raspberries & potatoes.
Measurements of flow.by
current meter.
Average flow- 4.30 sec.ft.
Time-4:25 p.m.to 6:10 p.m.
1% hours.

Quantity of water in ac. ft. 0.627.
Depth on land- 0.366 ft.or 4.39 inches.

The raspberries were irrigated by the furrow method, but the tract was so narrow that the surface was almost entirely flooded. At 5:30 the water was running off the West end, fromwhere it was conveyed ina waste ditch to thwe potatoes.

MEASURRHENTS

OF

WATER DIVERTED BY THE 'VARIOUS DIVERSIONS OF THE PROVO DIVISION

OF PROVO RIVER 1914.

Diversion No.P-102.

Remund ditch

Approximate Acreage...... 28. June 18,..... 1.38 sec.ft.

July 14....... " "

特殊格特特特特特特特特特特特特特特特

Diversion No.P-103

Michel Ditch.

Approximate Acreage..... 86.50 June 18....................... 3.89 sec.ft.

特特特特特特特特特特特特特特特特特特

Diversion No.P-104.

Spring Creek and Sage Brush

Approximate Acreage.....1200 June 16.......47.99 sec.ft.

July 1........36.34 " 1

July1436.34 " "

July 21..... 29.30 " "

August 20.....21.40 " "

Diversion No.B-100.

Midway Irrigation Company et al

Approximate Acreage.... 4100

June 15.....100 sce.ft. approximately. (no measuring devices in some canals)

uly 2..... 65.50 sce.ft.

July 16...... 65.50 sec.ft.

August 6......51.20 " "

August 28......47.20 " "

Diversion No.P-107.

Neason Ditch.

Approximate Acreage.......68.0

July 14..........0.00 sec.ft.

计计算计算符件设计设计设计设计设计设计设计设计

Diversion No.P-108.

Averett Ditch

Approximate Acreage.....21.09.

Diversion No.P-113. Snake Creek Ditch
Approximate Acraege30.20
July 2
July 17

Diversion No.P-114. Charleston-Midway Ditch.
Approximate Acreage 144.60
July 2 1.36 sec.ft. July 140.00 sec.fyt.

Diversion No.P-122.
Daybell Springs
Approximate Acreage250.0
July 154.27 sec.ft.
松松棒棒棒棒棒棒棒棒棒棒棒棒棒棒棒
Diversion No.P-105.
Charleston Irrigation Company (Upper Canal)
Approximate Acreage7000.0
June 17
July 14
August 2220.00 10.00
· 你也会会你你会会会会会会会会会会会会会会会会会会会会会会会会会会会会会会会会
Diversion No.P-124.
Charleston Irrigation Company (Lower Canal)
Approximate Acreage472.50 June 18
July 3
July 1527.20 " " August 2021.00 " "
July 2119.70 " " August 2221.00
20 20 40 40 40 40 40 40 40 40 40 40 40 40 40
Diversion No.P-125
Approximate Acreage455.0
June 18

特特价格特殊的特殊特特特特特特特特特特特特特特特特特特

Diversion No.P*XXX-S-F-1

Giles and Thomas Ditches (South Fork)

Approximate Acreage......75.0

June 26.....2.50 second-feet.

**

Diversion No.P-N-F-1

Conrad Brothers.

Approximate Acreage......Unknown.

June 26.....2.00 sec.ft.

特特特特特特特特特特特特特特特特特特特特特特特

Diversion No.P-N-F-2.

Wildwood Resort Company.

Approximate Acreage......8.0

Diversion No.P-1

Provo Reservoir Company.

Approximate Acreage......4800@

Day Sec.ft Day Sec.ft	BER.
3 100.51 6 80.00 1 76.50 1 6 26 94.50 68.00 77.00 5 30 80.00 13 74.00 3 77.00 5 80.00 68.50 7 4	
26 94.50 68.00 77.00 5 30 80.00 13 74.00 3 77.00 5 4 80.00 68.50 7 4	3.00
30 80.00 13 74.00 3 77.00 5 4 80.00 68.50 7 4	3.22
80.00 68.50 7	2.22
10 00 00	1.17
19 69.30 5 67.20	2.22
00.00	2.22
00 00 00	2.22
0.0 0.1 1.0	1.54
PA AN AA	9.24.
31 77.00 12 60.00	- 1171
57.20	
19 60.20	
65.20	
25 64.70	
62.70	
26 72.70	
30 62.70	

特殊特殊特殊特殊特殊特殊特殊特殊特殊特殊特殊特殊特殊特殊

Sego Irrigation Com pany.

Approximate Acreage......200.0

JUNE Day Sec ft.	JUI Day	LY Sec.ft		GUAT Sec. ft.	SEPT Day	EMBER. Sec.ft.
5 5.39 26 5.39	6 8 13 19 31	5.40 3.00 3.00 4.00 3.00 4.00 3.00 3.00	1 3 6 11 12 15 19 22 25 26 30	3.00 2.80 3.00 2.80 2.80 2.80 2.80 2.80 2.80 2.80	1 5 7 9 10 12 14	280 2.80 2.80 2.80 2.80 2.80

Diversion No.P-2

Approximate Acs. 900- Timpanogas Ganal Company.

	JUNE	J	ULY	A	UGUST	SE	ртемвто
Day 3 26	JUNE Sec.ft. 27.33 34.46	Day 6 8 13 19 82	Sec.ft. 30.00 29.00 22.50 29.00 22.50 18.40 18.00 17.80 18.00 20.00	Day 1 3 6 11 12 15	Sec.ft. 21.20 21.20 18.00 18.00 16.20 18.00 18.00 18.00 18.00	SE Day 1 7 9 12 14	PTEMBER. Sec.ft. 18.00 17.40 18.00 15.39 15.39
		30	19.00 18.00	25 26 30	16.00 14.25 14.60 18.00		

Diversion No.P-3.

Provo Bench Canal and Irrigation Company.

Acreage..... 4332.5

**	JUNE		JULY	A	UGUAT	SEPT	EMBER.
Day 3	Sec.ft. 136.10	Day	Sec.ft.	Day	Sec.ft.	Day	Sec.ft.
26		1	120.00	1	104.50	1	93.00
20	122.00	3	105.00		106.00		104.20
		13	107.00	3	104.00	7	101.50
			108.30		106.00	9	104.40
		19	87.00	5	101.30	10	79.73
			86.70		106 .00	12	72.85
		22	90.00	6	103.50	1.4	91.33
		25	88.50		106.00		02.00
		28	88.50	1.1	100.50		
			97.00		90.60		
		30	106.00	12	93.50		
				15	92.00		
					86.70		
				19	87.00		
				25	84.20		
					82.80		
				26	84.90		
				30	93.60		
		U.	UNDUNUNUNUNU				

榜替特於於於於特特特特於於於於特特特特特特於於於於於於非非非非非於於

Diversion No.P-4.

West Union Canal Company and Others.

Approximate Acreage.....1900.

J	UNE	Н	ULY	AUG	UST	SEP	TEMBER.
Day	Sec.ft	Day	Sec.ft.	Day	Sec.ft.	Day	Sec.ft.
3	53.34	6	42.90	1	40.90	1	37.80
25	58.02	8	43.80		37.80	7	42.28
		13	43.80	3	40.90		37.80
			47.50		37.80	12	35.16
		19	37.80	6	37.70	13	23.58
			38.00	11	37.80		
		22	39.12	12	37.80		
		25	38.52	15	43.80		
		30	37.80		37.80		
		31	37.80	19	34.00		
					37.80		
				25	37.80		
				26	37.80		
				30	37.80		

Diversion No.P-6.

Upper East Union Canal Company et al.

Approximate Acreage..... 900.0

JUNE	J	ULY	AUC	JUST	SEP	TEMBER.
Day Sec,ft.	Day	Sec.ft.	Day	Sec. ft.	Day	Sec.ft.
6 29.82	6	45.00	1	26.10	1	23.20
25 40.00	8	32.32		23.20	. 7	25.68
	13	32.32	3	27.20		23.20
	19	23.22		23,20	12	25.68
		25.00	6	23.20	1.4	15.00
	22	30.24	11	23.20		
	25	28.32	12	23,20		
		23.20	1.5	27.20		
	30	23.20		23.20		
	31	23.20	19	23.20		
			25	20.10		
				23.20		
			26	23.20		
			30	23.20		
		MARALANA SEALANA,	32.32.32.32.32.32.32.32.32.32.32.32.32.3	Mark of the Mark State of the State		

촦촦촦촦쁙촦촦촦촦촦놖놖놖놖놖촦촦촦촦촦촦촦촦촦

Diversion No.P-8.

Provo City.

Approximate Acreage.....2800 and Power.

JUNE	J	ULY	A	UGUST	SE	PTEMBER.
Day Sec ft.	Day	Sec.ft.	Day	Sec.ft.	Day	Sec.ft.
3 162.50	6	90.00	1	114.40	7	111.30
26 130.40		120.00		118.00		115.00
	8	135.00	3	90.90	12	100.93
		137.50		118.00	14	105.75
	13	137.50	6	131.70		
	18	80.10		118.00		
	19	103.00	11	101.80		
		115.00		115.00		
	22	119.00	12	118.08		
	25	115.50	15	98.95		
	28	118.00		115.00		
	31	118.00	19	129.95		
				115.00		
			25	120.70		
				115.00		
			26	115.00		
			30	115.00		

The above measurements include 8.33 sec.ft which is taken as the flow in the water-works system.

Diversion No.P-5.

East River Bottoms Water Company et al.

Approximate Acreage... 900.0

JUI Day 3 26	Sec.ft. 50.97 44.88	Day 6 8 13 18 19 22 25	Sec.ft. 29.78 37.46 37.46 22.50 18.46 18.00 26.40 26.40	Day 1 3 6 11 15 19 25 26 30	AUGUST Sec.ft. 18.00 33.00 18.00 20.90 18.00 24.90 30.80 26.30 24.50 26.30 24.50 26.30	7 20 19 19 12 29	MBER. ft. .96 .64 .52 .87
					26.30		
			2425353636		26.30		
			11 . 11 M. 11.	元元五五号号号号	****	44.44	

Diversion No.P-9.

Little Dry Creek Irrigation Co.

Approximate Acreage.....500.00

JUNE					•	
Day Sec.ft. 6 700 7.04 25 11.35	JU Day 6 8 13 19	Sec.ft. 10.93 6.86 6.86 9.63	Day 3 6	UGUST Sec.ft. 10.00 6.86 10.00 5.80	Day 1	Sec.ft. 7.00 9.63 7.00
	22 25	10.00 7.40 8.30	15	10.00	12	9.63 4.89
			19	10.00 5.80 10.00		
			25	4.90		
			26 30	9.63		
Diversion No.P-10).	****	****	***		

Lake Bottom Canal Company.

Approximate Acreage......1275.

Day 6 25	Sec.ft.	JULY Day Sec.ft.	AUGUST Day Sec.ft.	SEPTEMBER. Day Sec. ft.
	15.42		20 9.86	

Diversion No.P-11.

Fort Field Canal Bompany.

June 60.29 June 255.40	sec.ft.	July 8350	
20		July 8	11 11
		Aug. 267.03	u n

Diversion No.P-S-1 George Taylor Ditch.	
Approximate Acreage 16.50	
June 8 July 8 0.00 June 26 " " *****************************	
Diversion No.P-S-2.	
George and Ashted Taylor Ditch	
Approximate Acreage3.50	
July 8 0.00 Sec.ft.	
"你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你	
Diversion No.P-S-3. Partridge Ditch.	
Approximate Acreage 37.86.	
July 8	
你我你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你你	
Diversion No.P-S-4	
Stephen Jones Ditch	
Approximate Acreage8.00 July 80.00 sec.ft. August 260.00 sec ft	
\$1.46 46 46 46 46 46 46 46 46 46 46 46 46 4	
Diversion No.P-S-5. Roy Brown Ditch.	
Approximate Acreage70.0	
July 8	t.
Diversion No.P-S-6 Clyde Ditch	
Approximate Acreage75.00	
June 26	
1.31	
Diversion No.P-S-7.	
Approximate Acreage10.0	
June 26	
July 8	
Diversion No.P-S-8. Tanner Farm Ditches.	
Approximate AcreageUnknown. June 264.24 sec.ft. August 260.00	

ADMINISTRATION OF COURT ORDERS AND DECREES.

For the proper administration of the decrees of the Court, and the equitable distribution of the waters of Provo River thereunder, the following information and equipment should be available:

- (1) Requirements per acre served or "duty", during high and intermediate stages of the River.
- (2) Acreage irrigated under each diversion.
- (3) Priority of rights as a guide in low water.
- (4) Proper means for the measurement of water diverted.

As a guide to an agreement for the coming irrigation season(1915) your Commissioner has the following suggestions and recommendations to submit:-

- (1) That, pending a proper determination of "duty", a temporary agreement be entered into by the parties to this action.
- (2) That the acreage irrigated by each diversion be determined by a competent surveyor; and that a certificate signed by such, showing the acreage irrigated, be submitted by the users under each canal before the beginning of the irrigation season. At the present time, those cabals whose true acreage is known cannot be fairly allowed water on the same basis as those whose acreage is estimated; for the reason that the number of acres estimated by the users under any one canal is usually in excess of the truth.
- (3) The priority of right among the users of water from Provo River is fairly well defined, except in few cases, by Decrees of Court or by agreement among the trrigators.
- (4) That every canal which has not a proper device for the measurement of the water diverted be required to install such device before the
 beginning of the irrigation season. That in every case where conditions
 are favorable, a suppressed or a trapazoidal weir be required.

With the above mentioned information and equipment made available to the Commissioner, the cost of measurement and distribution will be very much reduced.

For the administration of the orders of the Court in this cause, for the year 1915, your Commissioner recommends the following organizationx-and personnel;-

- (1) A commissioner having charge of the entire River System, to begin his services not later than March 1st, in order to design and install proper measuring devices, where needed, before the beginning of the irrigation season. He could very well attend to all the necessary work until the time when it became necessary to distribute water to the various canals. After this time he could, with very little assistance, and with proper measuring devices, attend to the distribution in all of Wasatch and Summit Counties. He should have authority to employ assistants for short periods when necessary during the period of distribution.
 - (2) A commissioner, or deputy commissioner to have charge of the distribution of the water to the users in Utah County, to begin his services as soon as it becomes necessary to distribute water in the Provo district, which would probably be sometime in the month of June.
 - (3) A deputy commissioner or assistant located at the reservoirs of the Union Reservoir Company, to begin his services as soon as the reservoirs are filled, in order to keep a record of the natural outflow for as long a period as possible before the stored water is released; thus securing data upon which to base a calculation as to the probable natural outflow during the drawing period. These same data should be obtained for the Reservoir of the Washington Irrigation Company, either by the same Deputy or another assistant. Your Commissioner is of the opinion that one man could not attend to the two systems on accout of the distance between and ruggedness of the intervening country. The deputy or deputies should be competent to make proper measurements of streams by means of weir or current meter.

 and expenses of the commissioners

The payment for the services should be based on acreage and length of the irrigation season, since it is impossible to keep an accurate record of the water diverted by the small canals which use intermittantly.

The payments should be made by the Clerk of the Court out of a fund paid in advance by the parties to this action, according to the estimated share of each; the excess, if there be any being refunded at the end of the season. This method would relieve the Commissioners of the

trouble and annoyance of collecting a large number of small bills and permit of his devoting all his time to the more important work of measurement and distribution.

The Commissioner should be given authority to compel the installation of measuring devices, by acourt order giving him power, if necessary to have them installed at the expense of the users under the canal in any case of refusal or neglect to comply with his request. The users who are indifferent in this respect increase the expense and annoyance for those who comply with the requirement.

The proper distribution of water in the Provo district was made especially difficult during 1914 on account of a lack of information as to the rights of the East River Bottom Water Company and other users c claiming the right to water as "The Residents of The River Bottoms", as defined in the Morse Decree of this Court. Your Commissioner was unable to learn, from these users or from any other source, the division of this right between the above mentioned corporation or company and the individual users.

Since these users divert water into 17 small canals from the channel known as Gity Creek, through which Provo City draws its supply; it is very important that the rights of these two groups of users (The East River Bottom Water Company and other "Residents of The River Bottoms") be defined, and placed under proper regulation, in order to insure Provo City against irregularities in its supply, such as occurred during 1914.

Therefore your Commissioner recommends that (1) a proper weir be placed in City Creek near its head, to measure the total flow into this channel, and (2) that The East River Bottom Water Company and the other individuals mentioned above be required to define their rights by agreements or otherwise, and to furnish the Commissioner or other person suthorized to distribute the waters of the River each year, a copy of the schedule showing the time that each diversion will use water during that year.

2888

Report of Frank Henring.

FEB 13 1915

FEB 13 1915

6.1 Palluyman CLERK

Coffee Common DEPUTY